

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Listing of Claims

Claims 1 to 17 (cancelled).

18. (Currently amended) A mold of a type for dies and molding of articles using dies requiring heat to be taken from the mold from time to time, wherein the mold includes at least one completely closed chamber to provide a closed system and each said at least one completely closed chamber being provided with a single quantity of liquid therein which extends to cover at least one of the areas from which heat is to be taken, said single quantity of liquid being fed through and guided by a first conduit communicating with said closed chamber and a space above the single quantity of liquid and within each of said at least one completely closed chamber and a second conduit communicating with said closed chamber and the space above the single quantity of liquid to form a passageway for vapor to a condensing means, wherein pressure is set at a level which will enable the single quantity of liquid to boil at a selected temperature, and said single quantity of liquid communicates with said condensing means to effect, by cooling, condensation of the vapor or vapors from the single quantity liquid in the space flowing through said second conduit, the single quantity of liquid having a volume such that it has an upper level above one of the areas of the mold to be cooled and substantially only the vapor of the liquid within the chamber above the passageway and the upper level of the liquid so that the completely closed chamber keeps the same single quantity of liquid through the full cooling process and the total overall temperatures of the mold is kept relatively uniform and provides for effective heat transmission through the mold throughout the molding process.

19. (Currently amended) A mold as claimed in claim 18, wherein the chamber is shaped and positioned so that all of the working surfaces of the mold are serviced equally by the liquid therein and the single quantity liquid will have effective access to each of the areas of the mold from which heat is to be taken and the same single quantity of liquid [blows] flows back to the body of the liquid in the completely closed chamber.

20. (Currently amended) A mold as claimed in either [of] claim 18 or 19, wherein the single quantity of liquid is water only within the space in the chamber above the liquid level.

21. (Currently amended) A mold as claimed in either claim 18 or 19, wherein the mold is a mold for molding of plastic[s] materials.

22. (Previously presented) A mold as claimed in either claim 18 or 19, wherein the mold is a die for the mold casting of metals.

23. (Previously presented) A mold as claimed in either claim 18 or 19, wherein the mold is a mold for injection molding of plastic material.

24. (Previously presented) A mold as claimed in either claim 18 or 19, wherein the mold is a mold for molding by thermoforming of plastic materials.

25. (Previously amended and currently amended) A mold for dies and articles using dies having an internal cooling arrangement which is a completely closed chamber having therein a single quantity of liquid with a volume such that it has an upper level above at least some of the areas of the mold to be cooled and has substantially only the vapor or vapors of the liquid in a space within the chamber above the upper level of the

liquid and condensing means using the same single quantity liquid to effect, by cooling, condensation of the vapor or vapors of the liquid, said completely closed chamber being integrated with the mold, and total overall temperature of the mold is maintained relatively uniform and the cooling condenses the vapor or vapors derived from the single quantity of liquid used by the condensing means.

26. (Currently amended) A mold for injection molding of plastic materials for dies and articles using dies having an internal cooling arrangement which is a completely closed chamber partially filled with a single quantity of liquid having an upper level sufficient that at least some areas of the mold within the chamber adjacent to parts of the mold to be cooled are accessed by the single quantity of liquid when the mold is in use and provided in a space in the completely closed chamber above the liquid, there is only the vapor of the single quantity of liquid and condensing means within this space using the same single quantity of liquid in the completely closed chamber.

27. (Previously presented) A mold for injection molding of plastic materials for dies and articles using dies which provides for effective heat transmission throughout the mold, the mold having an internal cooling arrangement using a single cooling liquid and includes a completely closed chamber partially filled with the single cooling liquid with an upper level of sufficient height so that at least some areas of the mold within the completely closed chamber and adjacent parts of the mold to be cooled are accessed by the single cooling liquid when the mold is in use and, in a space in the chamber above the liquid, substantially only the vapor of the single cooling liquid, and an arrangement to provide cooling of any vapor using the single cooling liquid within the space in the chamber above the liquid level to effect at least some condensation of the vapor thereby

so that the overall temperature of the mold is kept relatively uniform and heat is dissipated by the cooling of the vapor.

28. (Previously presented) A mold as in preceding claim 25 where the liquid is water.

29. (Previously presented) A mold as in preceding claim 25 wherein the vapor is water vapor.

30. (Currently amended) A mold as claimed in [any one of the preceding] either claim[s] 26 or 27, wherein the mold is a die, and including at least a heating means located within the chamber within the liquid such that during a standby time, the temperature of the die or mold can be kept within a selected range of temperatures.

31. (Currently amended) A mold as claimed in claim 26 or 27 wherein the internal cooling arrangement additionally includes cooling means comprising a tube, a core in the tube and means to direct cooling water as the single quantity of liquid through the tube.

32. (Currently amended) A method of cooling of working parts of a mold for dies and articles using dies where the mold has at least one completely closed chamber having a single quantity of liquid therein which extends to cover at least one of the areas from which heat is to be taken, and a space above the single quantity of liquid and within the completely closed chamber in which pressure within the space is caused to be set at a level which will enable the single quantity of liquid to boil at a selected temperature, said selected temperature being at a level such that the temperature is below a temperature of the area from which heat is to be taken this being by reason of, as a first step, partially

filling each of said at least one completely closed chambers with the liquid and then extracting air above the liquid so that there is substantially only the vapor or vapors of the liquid within the completely closed chamber above the upper level of the liquid, and passing at a selected cooling temperature, liquid through condensing means to effect, by such cooling, condensation of vapor of the liquid in the space.

33. (Currently amended) A method of cooling of working parts of a mold for dies and molding of articles using dies where the mold has at least one completely closed chamber having a single quantity of liquid therein which extends to cover at least one of the areas from which heat is to be taken, each of said at least one completely closed chamber being integrated with the mold and a space above the single quantity of liquid and within the completely closed chamber in which pressure within the space is caused to be set at a level which will enable the single quantity of liquid to boil at a selected temperature, said selected temperature being at a level such that the temperature is below a temperature of the areas from which heat is to be taken this being by reason of, as a first step, filling of the completely closed chamber with the single quantity of liquid and then extracting a selected portion of the single quantity of liquid without allowing air to replace the [extracting] extracted liquid, and passing at a selected cooling temperature, the single quantity of liquid through condensing means to effect, by such cooling, condensation of vapor of the single quantity of liquid in the space.

34. (Currently amended) A method as claimed in claim 32 or 33 wherein the single quantity of liquid is water.